

Dawn HNBR DN3418

产品介绍

标准中高腈牌号，动态性能和加工性能优异，适用于同步带、O型圈、垫片、油封及石油工业配件等。

FEATURES

Standard medium & high ACN grade with excellent dynamic properties and processing, especially suited for synchronous belts , O-rings, gaskets, oil seals and oil industry accessories, etc.

常规信息 General information			
RoHS 符合性 RoHS compliance	符合 Complied		
状态 Status	固体 Solid		
物性参数 Performace Parameters	典型值 Typical Value	单位 Unit	方法 Method
碘值 Iodine Value	10-18	mg/100mg	SH/T 1763
饱和度Hydrogenation Degree	97	%	SH/T 1762
丙烯腈含量 Acrylonitrile Content	34.0±1.5	%	SH/T 1157.2
门尼粘度 Mooney Viscosity	80-95	ML ₁₊₄ 100°C	GB/T 1232.1
灰分 Total Ash	≤0.80	%	GB/T 4498.1方法A
挥发分 Volatile Matter	≤1.00	%	GB/T 24131.1烘箱B
山东道恩特种弹性体材料有限公司 Shandong Dawn Special Elastomer Material Co., Ltd. 地址：山东省烟台市龙口市新材料·新能源产业园 Address: New material and energy industrial park, Longkou city, Yantai city, Shandong Province. 电话：0086-535-8831057 Tel: 0086-535-8831057			